TCB

GRANT OF EQUIPMENT AUTHORIZATION

TCB

Certification

Issued Under the Authority of the Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp. 1274 Anvilwood Avenue Sunnyvale, CA 94089 Date of Grant: 09/24/2021

Application Dated: 09/24/2021

Seeed Technology Co., Ltd.
9F, G3 Building, TCL International E City,
Zhongshanyuan Road,Nanshan District
Shenzhen, 518055
China

Attention: Albert Miao , R&D Director

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: Z4T-RETERMINAL

Name of Grantee: Seeed Technology Co., Ltd.

Equipment Class: Part 15 Spread Spectrum Transmitter
Notes: reTerminal with Raspberry Pi Compute

Module CM4X

Frequency Output Frequency Emission

Grant Notes FCC Rule Parts Range (MHZ) Watts Tolerance Designator

CC 15C 2402.0 - 2480.0 0.0002

Output power listed is conducted.

CC: This device is certified pursuant to two different Part 15 rules sections.

TCB

GRANT OF EQUIPMENT AUTHORIZATION

TCB

Certification

Issued Under the Authority of the Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp. 1274 Anvilwood Avenue Sunnyvale, CA 94089 Date of Grant: 09/24/2021

Application Dated: 09/24/2021

Seeed Technology Co., Ltd.

9F, G3 Building, TCL International E City,
Zhongshanyuan Road,Nanshan District
Shenzhen, 518055
China

Attention: Albert Miao , R&D Director

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: Z4T-RETERMINAL

Name of Grantee: Seeed Technology Co., Ltd.

Equipment Class: Digital Transmission System

Notes: reTerminal with Raspberry Pi Compute

Module CM4X

Frequency Output Frequency Emission

Grant Notes

CC

FCC Rule Parts
Range (MHZ)
Watts
Tolerance
Designator

2402.0 - 2480.0
0.0027

CC 15C 2412.0 - 2462.0 0.0073

Output power listed is peak conducted. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. Users and installers must be provided with antenna installation instructions and transmitter operating conditions for satisfying RF exposure compliance. This device supports 20/40 MHz bandwidth modes.

CC: This device is certified pursuant to two different Part 15 rules sections.